

MICRO H-2 W BLASER SADDLE MOUNT

AIMPOINT® MICRO H-2 BLASER SADDLE MOUNT



AIMPOINT® MICRO H-2 BLASER SADDLE MOUNT

Aiming dot size	2 MOA
Battery type	3V lithium battery, type CR2032.
Battery life - Day time use	50 000h (over 5 years of continuous use)

OVERVIEW

The Aimpoint® Micro H-2 redefines everything you thought you knew about compact red dot sights. The Aimpoint® Micro H-2 (2MOA) sight has been paired with Blaser original saddle mount manufactured by Blaser to create this package.

The Aimpoint Micro H-2 with Blaser original saddle mount is only available as a kit.

Launched 2015.

AIMPOINT® MICRO H-2 WITH MOUNT FOR BLASER RIFLES

This alternative configuration utilizes both of the mounting points featured on Blaser rifle barrels. Quick detach levers allow this sight to be mounted and dismounted quickly, and without loss of zero.

This mount fits on all Blaser guns with the Blaser saddle mount interface.

AIMPOINT® MICRO H-2

The extremely compact Micro H-2 offers up to five years of constant on power from a single CR-2032 battery, and has 12 brightness settings for optimal performance in any light conditions. This sight is completely waterproof, and is a result of feedback coming from hard core customers desiring an even more hard core Micro sight. With a redesigned and reinforced house body, as well as flip-up covers protecting the lenses, the Micro H-2 can withstand all types of environmental conditions. And thanks to new optical lenses and cutting edge lens coatings, the optical performance and the shape and clarity of the red dot are radically improved.

MICRO H-2 W BLASER SADDLE MOUNT

AIMPOINT® MICRO H-2 BLASER SADDLE MOUNT

TECHNICAL SPECIFICATIONS

GENERAL SPECIFICATIONS	POWER SOURCE	ENVIRONMENTAL SPECIFICATIONS
Art.No: 200187	Battery type: 3V lithium battery, type CR2032.	Temperature range operation: -30°C to 60°C (-20°F to 140°F)
OPTICAL SPECIFICATIONS	Battery life - Day time use: 50 000h (over 5 years of continuous use)	Temperature range storage: -51°C to 71°C (-60°F to 160°F)
Operating principle: Reflex collimator sight with LED	Power intensity: 1 Off position and 12 daylight settings	Temperature shock: Operable after a temperature shock between -45°C and +71°C. Duration: 4h of Hot +71°C, 4h of Cold -45°C. Cycling: 3 times
Optical magnification: 1x		Humidity: Operates despite humidity. Limits: RH: 95%, Temp: 20°C to 50 °C, cyclic
Aiming dot size: 2 MOA		Immersion, static: Submersible to 15 ft, 5 m
Dot intensity: Visible against a background luminance of 0.1 to 55 000 lx		Shock: Blaser Mount not shock tested
Dot color: Peak Wavelength: 650 ± 10 nm		Vibration: Blaser Mount not vibration tested
NVD compatible: No		Chemical resistance: Blaser Mount not tested for chemical resistance
Optical coating: Anti-reflex, all surfaces and multi-layer.		
Clear aperture: 18 mm		
Eye relief: Unlimited		
PHYSICAL SPECIFICATIONS		
	Length sight only: 68 mm (2 5/8")	
	Length conf: 88 mm (3 7/16")	
	Width: 41 mm (1 9/16")	
	Height sight only: 36 mm (1 3/8")	
	Height conf: 47 mm (1 13/16")	
	Weight sight only (incl battery): 94 g, (3,3 oz)	
	Weight conf: 243 g (8,6 oz) incl mount	
	Housing material: High strength Aluminum	
	Housing finish and color: Semi-matte black	
	Material mount and spacer std conf: High strength Aluminum	
	Surface treatment: Anodized, semi matte	
	Height of optical axis - sight and mount: 20 mm (3/4") over top surface of Picatinny/Weaver Rail	
	Height of optical axis - sight, mount and low spacer: Spacer low: 50 mm (1 15/16") over top surface of Picatinny/Weaver Rail	
	Height of optical axis - sight, mount and high spacer: Spacer high: 59 mm (2 5/16") over top surface of Picatinny/Weaver Rail	
	Adjustment: Range ±1 m at 100 meters (±1 yds at 100 yds) in windage and elevation, 1 click = 13 mm at 100 meters = 10 mm at 80 meters = 7/16" at 100 yds	