

LE10 3.0

Thermal Monocular



The LE10 3.0 is the ultimate-valued thermal monocular for close-range observation. Featuring a 256×192 thermal detector and a 9.7 mm F1.0 lens, it offers a 1.4× base magnification and an 18° field of view, with a detection range of up to 500 m. Compact, reliable, and lightweight, it is an excellent choice for quick and efficient use in tight spaces.

● Key Feature

- High-sensitivity thermal module with NETD<20 mK (@25°C, F# = 1.0).
- 9.7 mm, F1.0 lens with thermal detection range up to 500 m
- AI-powered Image Pro 3.0 algorithm
- HIKMICRO Shutterless Imaging System (HSIS)
- 0.39-inch OLED display with 1024×768 resolution
- Replaceable and rechargeable 18650 battery provides up to 5.5 hours of continuous operation at -20°C
- Lightweight design at 291.5 g, with a pocket-sized build

• Specification


Thermal Module	
Image Sensor	VOx Uncooled Focal Plane Arrays
Max. Resolution	256×192
Frame Rate	50 Hz
Pixel Interval	12 μm
Response Waveband	8 μm to 14 μm
NETD	Less than 20 mK (@25°C),F#=1.0
Lens (Focal Length)	9.7 mm, f1.0
Focus Mode	Focus Free
Detection Range	500 m
Min. Focusing Distance	3.4 m
Magnification	1.4× - 11.2× (8×)
Field of View(H × V), Degrees / m @100m	18.0°×13.6°/31.7 m×23.8 m
Image Display	
Display	1024×768, 0.39-inch, AMOLED
Palettes	Black Hot, White Hot, Red Hot, Fusion, Red Monochrome, Green Monochrome
Exit Pupil	6 mm
Eye Relief	20 mm
Diopter (Range)	-5D to +3D
Brightness Adjustment	Yes
Tone Adjustment	Cold, Warm
Contrast Adjustment	Yes
Zoom Pro	N/A
HSIS (HIKMICRO Shutterless Image System)	Yes
Image Pro 3.0	Yes
Sync Pro	Yes
System	
Record Video	Yes
Capture Snapshot	Yes
Audio Recording	Yes
Standby Mode	Yes
Built-in Memory	Built-in EMMC (64 GB)
PIP	Yes
Hotspot	2.4 GHz/5 GHz Wi-Fi Waveband
Hot Track	Yes
Distance Measurement	Yes
Local Album	Yes

Power Supply	
Battery Type	Replaceable and Rechargeable Li-ion 18650 Battery
Battery Operating Time	6-hour continuous running with hotspot on (@25°C) 5.5-hour continuous running with hotspot on (@-20°C)
Type-C Power Supply	DC 5V/2A Supports External Power Supply, Support Direct Charging
General	
Protection Level	IP67
Dimension	152.4×53.6×49.5 mm
Weight	291.5 g with battery
Working Temperature	From -30°C to 45°C (-22°F to 113°F); Humidity: 90% or Less

• Available Model

HM-TSF2-10Y1G/W1-LE10 3.0

• Dimension



Unit:mm[Inch]

▪ Accessories



Battery Charger (×1)




Battery (×2)



Lint-Free Cloth (×1)



Type-C Cable (×1)



Quick Start Guide(×1)

COMPLIANCE NOTICE: The thermal series products might be subject to export controls in various countries or regions, including without limitation, the United States, European Union, United Kingdom and/or other member countries of the Wassenaar Arrangement. Please consult your professional legal or compliance expert or local government authorities for any necessary export license requirements if you intend to transfer, export, re-export the thermal series products between different countries.



 Hikmicro Hunting.Global  HIKMICRO Outdoor  www.hikmicrotech.com  [hikmicro_hunting_global](https://www.instagram.com/hikmicro_hunting_global)  HIKMICRO  info@hikmicrotech.com

Room 313, Unit B, Building 2, 399 Danfeng Road, Xixing Subdistrict, Binjiang District, Hangzhou, Zhejiang
© Hangzhou Microimage Software Co., Ltd. All rights reserved. | Data subject to change without notice!